



# THE EVOLUTION OF POWER

## SEE THIS MACHINE ON THE FIELD



# FOR COMPLEMENTARY TECHNICAL INFORMATION, ACCESS OUR WEBSITE WWW.TMAMAQUINAS.COM.BR

# **CTX 19000** Filter cake cart

It stands out for its functionality, operational performance and sturdiness. Pulled by tractors with high-flotation tires, it performs two planting rows simultaneously, furrowing operations and filter cake distribution.

### **TECHNICAL SPECIFICATIONS**

VOLUMETRIC CAPACITY	19 m³ [670,98 ft³]
VOEDMETRIC CALACITY	
LOADING CAPACITY	20.000 kg [44092.45 lbS]
LOADING HEIGHT	3.200 mm [10.4987 ft]
TIRES OUTER WIDTH	3.600 mm [11.811 ft]
EQUIPMENT LENGTH	9.200 mm [30.1837 ft]
HIGH-FLOTATION TIRES	600 / 50 - 22.5"
SUSPENSION	TANDEM
GAUGE 2.400 / 2.800 / 3.000 mr	m [7.874 / 9.1 864/ 9.8425 ftp]
POWER PLANTING ROW APPLICAT	TON 230 HP
POWER FILTER CAKE APPLICATION	N 290 HP



ENGINEERING RESERVES THE RIGHT TO MAKE TECHNICAL CHANGES WITHOUT PRIOR NOTICE

3100, Thomaz Alberto Whately Av. Pq. Ind. Coronel Quito Junqueira 14075-380 - Ribeirão Preto/SP Corporate TMA: | Technical Assistance WhatsApp: +5516 3969.4933 | +5516 99772.5083 Business WhatsApp:

+5516 99629.7181 WWW.TMAMAQUINAS.COM.BR

# MAIN ADVANTAGES

- Two furrowers with containment box.
- Suggested planting speed: 5 to 6 km/h.
- Planting spacing: 0.90 to 1.5 m [2.9 to 4.9 ft] and double alternating 0.90 to 1.6 m [2.9 to 5.2 ft].
- > Depth limiting wheel: regulation as needed.
- Distribution: two steel conveyor belts driven by hydraulic engine with application adjustment.
- Coverer with adjustable arms and 4 concave discs with angle and height regulation by hydraulic cylinders.
- High-flotation tires: 600 / 50 22.5".
- PinBall type frontal hitch system.
- Header with hydraulic suspension system.
- Furrowers allow regulation for planting spacing, furrow's depth and width.
- Wheel set: Tandem axle system with high-flotation and low-pressure tires, which contributes to the reduction of soil compaction.
- Technical Assistance TMA.

### **OPTIONALS**

- Moldboard plow.
- Fertilizer deposit capacity of 700 kg.
- Worm thread in surface application in 4 or 6 simultaneous row.
- Central tire inflation system.
- Oxide box with conveyor belt.



BNDES



