



**AFTER SALES**  
**TMA**

Always a differential.

# THE EVOLUTION OF POWER



**WATCH OUR SUGAR CANE WAGON**

**THE BEST OF MANEUVERABILITY**

**CIRCULAR MANEUVER**





# VTX 5022 S SUGAR CANE WAGON

TMA sugar cane wagon stands out for its robustness and operational performance. Its structure is designed to support the most severe working conditions.

## Some of its advantages are:

- ▶ The largest actual volume available in the cargo basket.
- ▶ Shorter maintenance cycle.
- ▶ The smallest turning radius on the market.
- ▶ Load elevator with favorable angle for filing.
- ▶ Greater reach on the transport trailer, centralizing the load.

## TECHNICAL SPECIFICATIONS

TOTAL WIDTH	4.000 mm
TOTAL LENGTH WITH HEADER	9.200 mm
TOTAL HEIGHT	3.965 mm
SWING HEIGHT	5.150 mm
HEIGHT IN LOADING	4.800 mm
GAUGE	2.800 mm / 3.000 mm
HIGH-FLOTATION TIRES	600/50R-22.5 RADIAL
VOLUMETRIC CAPACITY	46 m <sup>3</sup>
HEAPED VOLUMETRIC CAPACITY	48 m <sup>3</sup>
LOADING CAPACITY	20.000 kg to 22.000kg
TOTAL WEIGHT	12.600 kg
REQUIRED POWER	180 cv
HYDRAULIC FLOW	120 L/min

## TMA EXCLUSIVE TRIDEM SUSPENSION

- ▶ 30° steering on the axles.
- ▶ Axles manufactured with high-strength materials and a capacity of 12.5 t each.
- ▶ Robust spring beams with reinforced balance system.
- ▶ Tubeless brake system with double springs and 8" brake lining.
- ▶ Brakes available on second and third axles.
- ▶ 40L Air Reservoir.
- ▶ Relay Valve.
- ▶ Discharge valve.
- ▶ Safety System.

## HYDRAULIC CIRCUIT

- ▶ Hydraulic cylinders 5" x 3.1/2" x 2.000 mm.
- ▶ Safety valve approved to meet the NR 12 safety standard.
- ▶ Hydraulic hoses sized to meet the NR 12 safety standard.

## ELECTRIC CIRCUIT

- ▶ Auxiliary LED headlights.
- ▶ Siren reverse gear horn.
- ▶ LED flashlight lamp.
- ▶ 6-pin or standard tractor plugs.

## HEADER

- ▶ Reinforced header with ø100mm pinball coupling and fixing flange.
- ▶ Safety Chain.
- ▶ Support leg.

## LOAD ELEVATOR

- ▶ Sturdy rectangular structure.
- ▶ Pulleys with treated and lubricated bushings.
- ▶ Bearing with special bushings, without need for lubrication.
- ▶ Safety pin with padlock for maintenance.

## LOAD TANK

- ▶ The highest volumetric capacity of the market (auditable).
- ▶ Produced with QDR tubes with higher moment of inertia and less weight.
- ▶ Expanded upper plate and plain baseboard for better drainage.

## OPTIONALS:

- ▶ WHEEL CALIBRATION SYSTEM ®.
- ▶ Adjustable header.



3100, Thomaz Alberto Whately Av.  
Pq. Ind. Coronel Quito Junqueira  
14075-380 - Ribeirão Preto/SP

Corporate TMA: +5516 3969.4933 | Technical Assistance WhatsApp: +5516 99772.5083

Business WhatsApp: +5516 99629.7181

WWW.TMAMAQUINAS.COM.BR



MADE IN  
BRAZIL

