



Always a differential.

# THE EVOLUTION OF FORCE



SEE THIS MACHINE ON THE FIELD

THE BEST  
OF MANEUVERABILITY

CIRCULAR  
MANEUVER





# VTH 5022

## SUGAR CANE WAGON

TMA sugar cane wagon stands out for its robustness and operational performance. Its structure is designed to support the most severe working conditions.

### SOME OF ITS ADVANTAGES ARE:

- ▶ The largest actual volume available in the 50m<sup>3</sup> auditable cargo basket: approximately 22.000kg.
- ▶ Shorter maintenance cycle.
- ▶ The smallest turning radius on the market.
- ▶ Load elevator with favorable angle for filing.
- ▶ Greater reach on the transport trailer, centralizing the load.

### TECHNICAL SPECIFICATIONS

TOTAL WIDTH	3.740 mm
TOTAL LENGHT WITH HEADER	9.810 mm
TOTAL HEIGHT	3.965 mm
SWING HEIGHT	5.510 mm
LOADING HEIGHT	4.800 mm
GAUGE	2.400 mm / 2.800 mm / 3.000 mm
HIGH-FLOTATION TIRES	600/50-22.5 DIAGONAL
HEAPED VOLUMETRIC CAPACITY	50 m <sup>3</sup>
LOADING CAPACITY	21.000 kg a 23.000 kg
TOTAL WEIGHT	13.800 kg
REQUIRED POWER	150 HP
HYDRAULIC FLOW	120 L/min

### TMA EXCLUSIVE QUADREM SUSPENSION

- ▶ 30° steering on the axles.
- ▶ Axles manufactured with high-strength materials and a capacity of 12.5 t each
- ▶ Robust spring beams with reinforced balance system.
- ▶ Tubeless brake system with double springs and 8" brake lining.
- ▶ 40L Air Reservoir.
- ▶ Relay valves.
- ▶ Safety valve.
- ▶ Safety system.

### HYDRAULIC CIRCUIT

- ▶ Hydraulic cylinder ø3.1 x ø2X5" x 2.000 mm with 25000 kg lift capacity each.
- ▶ Safety valve approved to meet the NR 12 safety standard.
- ▶ Hydraulic hoses sized to meet the NR 12 safety standard.

### ELECTRIC CIRCUIT

- ▶ Auxiliary LED headlights.
- ▶ Siren reverse gear horn.
- ▶ LED flashlight lamp.
- ▶ 6-pin or standard tractor plugs.

### HEADER

- ▶ Reinforced header with ø100mm pinball coupling and fixing flange.
- ▶ Safety Chain.
- ▶ Support leg.

### LOAD ELEVATOR

- ▶ Sturdy rectangular structure.
- ▶ Pulleys with treated and lubricated bushings.
- ▶ Bearing with special bushings, without need for lubrication.
- ▶ Safety pin with padlock for maintenance.

### LOAD TANK

- ▶ The highest volumetric capacity of the market (auditable).
- ▶ Produced with QDR tubes with higher moment of inertia and less weight.
- ▶ Expanded upper plate and plain baseboard for better drainage.

### OPTIONALS:

- ▶ WHEEL CALIBRATION SYSTEM®.
- ▶ Adjustable header.
- ▶ Planter loading kit.

Version updated in April 2025



3100, Thomaz Alberto Whately Av.  
Pg. Ind. Coronel Quito Junqueira  
14075-380 - Ribeirão Preto/SP  
Corporate TMA: +5516 3969.4933 | Technical Assistance WhatsApp: +5516 99772.5083  
Business WhatsApp: +5516 99629.7181  
WWW.TMAMAQUINAS.COM.BR



MADE IN  
BRAZIL

